Attachments / Tilt-Tatch™ **Specifications**

Standard Optional N/A Not Applicable

Tilt-Tatch

ullet General

| Operating Weight | 145 kg |
|------------------|----------------|
| Length | 109 mm |
| Width | 1219 mm |
| Height | 518 mm |
| Cylinder Bore | 57 mm |
| Cylinder Rod | 25 mm |
| Cylinder Stroke | 107 mm |
| Cylinders | 1 |
| Oscillation | +/- 15 degrees |

ullet Compatible Carriers

| Skid-Steer Loaders | |
|--------------------|--|
| Bobcat S450 | |
| Bobcat S510 | |
| Bobcat S530 | |
| Bobcat S550 | |
| Bobcat S570 | |
| Bobcat S590 | |
| Bobcat S595 | |
| Bobcat S630 | |
| Bobcat S650 | |

| Compact Track Loaders | |
|-----------------------|--|
| Bobcat T450 | |
| Bobcat T550 | |
| Bobcat T590 | |
| Bobcat T595 | |

| Toolcat™ Work Machine | |
|-----------------------|--|
| Bobcat Toolcat 5600 | |
| Bobcat Toolcat 5610 | |

Compact Tractors

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.