



Specifications

■ Standard
 Optional
N/A Not Applicable

Concrete Pump

⊖ General

Operating Weight	998 kg
Length	2614 mm
Width	1217 mm
Height	1394 mm
Concrete Cylinder Diameter	152 mm
Concrete Cylinder Stroke	610 mm
Maximum Aggregate Size	38 mm
Maximum Concrete Pressure	5,171 cbar
Swing Tube Diameter	127 mm
Swing Valve Cylinder Diameter	76 mm
Swing Valve Cylinder Stroke	152 mm
Pumping Cylinder Diameter	76 mm
Pumping Rate	Up to 30 cu. Yd. (23 cu. M.) per hour*
Vertical Pumping Height	15,24 m
Horizontal Pumping Distance	76,2 m
Hopper Capacity	0,28 m ³

⊖ Compatible Carriers

Skid-Steer Loaders	
Bobcat A770	■
Bobcat S550	■
Bobcat S570	■
Bobcat S590	■
Bobcat S595	■
Bobcat S630	■
Bobcat S650	■
Bobcat S740	■
Bobcat S750	■
Bobcat S770	■
Bobcat S850	■
Compact Track Loaders	
Bobcat T550	■
Bobcat T590	■
Bobcat T595	■
Bobcat T630	■
Bobcat T650	■
Bobcat T740	■
Bobcat T750	■
Bobcat T770	■
Bobcat T870	■

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.